

Rekta 40x70 Direct - MPO - HO 325mA - RAL  
05.09214653-9999

#### Fixture details

|                 |                           |
|-----------------|---------------------------|
| Mounting        | Ceiling                   |
| Light emission  | Direct                    |
| Fitting cover   | micro prismatic diffuser  |
| Protection rate | IP 20                     |
| Housing         | Aluminium                 |
| Finish          | RAL colour at your choice |
| Certificates    | CE, ISO 9001              |

#### Electric details

|                  |                        |
|------------------|------------------------|
| Protection class | I                      |
| Supply           | 230V                   |
| Control gear box | Current driver DALI/TD |

#### Lamp details

|                     |                   |
|---------------------|-------------------|
| Lamptype            | LED 3000K         |
| Wattage             | 7,1W              |
| Gross luminous flux | 6725              |
| Luminaire power     | 39,3W             |
| Number              | 5                 |
| Lifetime LED module | L80/B10 > 102000h |
| Color tolerance     | MacAdam 3         |
| CRI                 | >80               |

#### Photometric details



|              |                 |
|--------------|-----------------|
| UGR          | >19             |
| CIE Fluxcode | 58 89 98 100 50 |

#### Dimensions

|   |         |
|---|---------|
| A | 1410 mm |
|---|---------|

#### Remarks

Ceiling luminaire - Direct - HO 325mA - MPO - RAL



A

B

C

D

E

F

G

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ

kWh/1000h

MULTILINE®

2019/2015