

Anilo Direct - satin - HO - RAL 9003  
04.49000224-9003

#### Fixture details

|                 |                       |
|-----------------|-----------------------|
| Mounting        | Pendant               |
| Light emission  | Direct                |
| Fitting cover   | Opal diffuser         |
| Protection rate | IP 20                 |
| Housing         | Aluminium             |
| Finish          | RAL 9003 Signal white |
| Certificates    | CE, ISO 9001          |

#### Electric details

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

#### Lamp details

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 70W              |
| Luminaire power         | 70W              |
| Luminaire luminous flux | 5990             |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

#### Photometric details



|              |                  |
|--------------|------------------|
| UGR          | >19              |
| CIE Fluxcode | 47 78 95 100 100 |

#### Dimensions

|   |         |
|---|---------|
| A | 1200 mm |
|---|---------|

#### Remarks

Suspended luminaire - Direct - satin - HO - RAL 9003





Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.



WXYZ  
kWh/1000h

2019/2015